

**FAG****HCB7216-C-T-P4S-UL**

## Spindle bearing

Spindle bearing HCB72...-C, adjusted, in pairs or sets, contact angle  $\alpha = 15^\circ$ , with ceramic balls, restricted tolerances

## Technical information



## Your current product variant

Contact angle	C	Contact angle $15^\circ$
Type of Seal	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing
Preload class	L	Preload light

## Main Dimensions &amp; Performance Data

d	80 mm	Bore diameter
D	140 mm	Outside diameter
B	26 mm	Width
$C_r$	94.000 N	Basic dynamic load rating, radial
$C_{0r}$	52.000 N	Basic static load rating, radial
$C_{ur}$	4.000 N	Fatigue load limit, radial
$n_G$ Grease	12.000 1/min	Limiting speed for grease lubrication
$n_G$ Oil	19.000 1/min	Limiting speed for oil lubrication
$\approx m$	1,163 kg	Weight





### Mounting dimensions

$d_a$	91 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	129 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	2 mm	Maximum recess radius
$r_{a1 \max}$	1 mm	Maximum recess radius
$E_{tk \min}$	100,5 mm	Minimum diameter injection pitch
$E_{tk \max}$	105,3 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	100,5 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	105,3 mm	Maximum diameter injection pitch
$a$	27,7 mm	Distance between the apexes of the pressure cones

### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
$\alpha$	15 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.



### Additional information

$F_{VL}$	293 N	Preload force light
$F_{VM}$	968 N	Preload force medium
$F_{VH}$	1.979 N	Preload force heavy
$K_{aEL}$	876 N	Lift-off force light
$K_{aEM}$	3.068 N	Lift-off force medium
$K_{aEH}$	6.618 N	Lift-off force heavy
$c_{aL}$	82 N/ $\mu$ m	Axial rigidity light
$c_{aM}$	134 N/ $\mu$ m	Axial rigidity medium
$c_{aH}$	187 N/ $\mu$ m	Axial rigidity heavy

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed