

**FAG****HS7022-C-T-P4S-UL**

## High speed spindle bearing

High speed spindle bearing HS70...-C, adjusted, in pairs or sets, contact angle  $\alpha = 15^\circ$ , restricted tolerances

## Technical information



## Your current product variant

Contact angle	C	Contact angle $15^\circ$
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing
Preload class	L	Preload light

## Main Dimensions &amp; Performance Data

d	110 mm	Bore diameter
D	170 mm	Outside diameter
B	28 mm	Width
$C_r$	48.000 N	Basic dynamic load rating, radial
$C_{0r}$	38.000 N	Basic static load rating, radial
$C_{ur}$	3.400 N	Fatigue load limit, radial
$n_G$ Grease	12.000 1/min	Limiting speed for grease lubrication
$n_G$ Oil	18.000 1/min	Limiting speed for oil lubrication
$n_G$	18.000 1/min	Limiting speed
$\approx m$	2,076 kg	Weight





### Mounting dimensions

$d_a$	121 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	159 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	2 mm	Maximum recess radius
$r_{a1 \max}$	1 mm	Maximum recess radius
$E_{tk \min}$	133,3 mm	Minimum diameter injection pitch
$E_{tk \max}$	136,5 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	129,2 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	136,5 mm	Maximum diameter injection pitch
$a$	32,8 mm	Distance between the apexes of the pressure cones

### Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
$\alpha$	15 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.



### Additional information

$F_{VL}$	168 N	Preload force light
$F_{VM}$	503 N	Preload force medium
$F_{VH}$	1.005 N	Preload force heavy
$K_{aEL}$	499 N	Lift-off force light
$K_{aEM}$	1.566 N	Lift-off force medium
$K_{aEH}$	3.257 N	Lift-off force heavy
$c_{aL}$	77 N/ $\mu$ m	Axial rigidity light
$c_{aM}$	121 N/ $\mu$ m	Axial rigidity medium
$c_{aH}$	164 N/ $\mu$ m	Axial rigidity heavy

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed