

**FAG****HS71907-E-T-P4S-UL**

## High speed spindle bearing

High speed spindle bearing HS719.-E, adjusted, in pairs or sets, contact angle  $\alpha = 25^\circ$ , restricted tolerances

## Technical information



## Your current product variant

Contact angle	E	Contact angle 25°
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing
Preload class	L	Preload light

## Main Dimensions &amp; Performance Data

d	35 mm	Bore diameter
D	55 mm	Outside diameter
B	10 mm	Width
$C_r$	6.100 N	Basic dynamic load rating, radial
$C_{0r}$	3.600 N	Basic static load rating, radial
$C_{ur}$	380 N	Fatigue load limit, radial
$n_G$ Grease	32.000 1/min	Limiting speed for grease lubrication
$n_G$ Oil	50.000 1/min	Limiting speed for oil lubrication
$n_G$	50.000 1/min	Limiting speed
$\approx m$	76,08 g	Weight





### Mounting dimensions

$d_a$	40 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	51,5 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,6 mm	Maximum recess radius
$r_{a1 \max}$	0,15 mm	Maximum recess radius
$E_{tk \min}$	42,6 mm	Minimum diameter injection pitch
$E_{tk \max}$	43,4 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	41,2 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	43,4 mm	Maximum diameter injection pitch
$a$	15,5 mm	Distance between the apexes of the pressure cones

### Dimensions

$r_{\min}$	0,6 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
$\alpha$	25 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.



### Additional information

$F_{VL}$	38 N	Preload force light
$F_{VM}$	113 N	Preload force medium
$F_{VH}$	226 N	Preload force heavy
$K_{aEL}$	109 N	Lift-off force light
$K_{aEM}$	333 N	Lift-off force medium
$K_{aEH}$	680 N	Lift-off force heavy
$c_{aL}$	61 N/ $\mu\text{m}$	Axial rigidity light
$c_{aM}$	91 N/ $\mu\text{m}$	Axial rigidity medium
$c_{aH}$	119 N/ $\mu\text{m}$	Axial rigidity heavy

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed