

**FAG****HSS71901-E-T-P4S-UL**

High speed spindle bearing

High speed spindle bearing HSS719..-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, lip seals on both sides, non-contact, restricted tolerances

Technical information



Your current product variant

Contact angle	E	Contact angle 25°
Sealing	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to DIN 620
Arrangement bearing set	U	Single bearing
Preload	L	Preload light
Lubricant	GA21	Grease for super precision bearings, standard

Main Dimensions & Performance Data

d	12 mm	Bore diameter
D	24 mm	Outside diameter
B	6 mm	Width
C_r	1.760 N	Basic dynamic load rating, radial
C_{0r}	690 N	Basic static load rating, radial
C_{ur}	73 N	Fatigue load limit, radial
n_G Grease	85.000 1/min	Limiting speed for grease lubrication
n_G	130.000 1/min	Limiting speed
$\approx m$	13 g	Weight



Mounting dimensions

d_a	15 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	21,5 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,3 mm	Maximum recess radius
$r_{a1 \max}$	0,1 mm	Maximum recess radius
a	7,2 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	0,3 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	80 °C	Operating temperature max.

Additional information

F_{VL}	11 N	Preload force light
F_{VM}	33 N	Preload force medium
F_{VH}	67 N	Preload force heavy
K_{aEL}	32 N	Lift-off force light
K_{aEM}	99 N	Lift-off force medium
K_{aEH}	203 N	Lift-off force heavy
c_{aL}	23 N/μm	Axial rigidity light
c_{aM}	35 N/μm	Axial rigidity medium
c_{aH}	46 N/μm	Axial rigidity heavy



Characteristics



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides