


**FAG****HSS71926-E-T-P4S-UL**

High speed spindle bearing

High speed spindle bearing HSS719..-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, lip seals on both sides, non-contact, restricted tolerances

Technical information



Your current product variant

Contact angle	E	Contact angle 25°
Type of Seal	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to DIN 620
Arrangement bearing set	U	Single bearing
Preload	L	Preload light
Lubricant	GA21	Grease for super precision bearings, standard

Main Dimensions & Performance Data

d	130 mm	Bore diameter
D	180 mm	Outside diameter
B	24 mm	Width
C _r	38.500 N	Basic dynamic load rating, radial
C _{0r}	34.500 N	Basic static load rating, radial
C _{ur}	2.950 N	Fatigue load limit, radial
n _G Grease	9.000 1/min	Limiting speed for grease lubrication
n _G	14.000 1/min	Limiting speed
≈m	1,665 kg	Weight



Mounting dimensions

d_a	139 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	171 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,6 mm	Maximum recess radius
$r_{a1 \max}$	0,6 mm	Maximum recess radius
a	48,1 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	1,5 mm	Minimum chamfer dimension
$r_{1 \min}$	1,5 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	80 °C	Operating temperature max.

Additional information

F_{VL}	224 N	Preload force light
F_{VM}	673 N	Preload force medium
F_{VH}	1.346 N	Preload force heavy
K_{aEL}	645 N	Lift-off force light
K_{aEM}	1.968 N	Lift-off force medium
K_{aEH}	4.004 N	Lift-off force heavy
c_{aL}	205 N/μm	Axial rigidity light
c_{aM}	303 N/μm	Axial rigidity medium
c_{aH}	393 N/μm	Axial rigidity heavy



Characteristics



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides