

**FAG****VCM7010-C-T-P4S-UL-XL**

High speed spindle bearing

High speed spindle bearing VCM70..-C, adjusted, in pairs or sets, contact angle $\alpha = 17^\circ$, with ceramic balls, rings made from Vacrodur, restricted tolerances

Technical information



Your current product variant

Contact angle	Contact angle 17°	Contact angle 17°
Type of seal	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to DIN 620
Arrangement bearing set	U	Single bearing
Preload	L	Preload light

Main Dimensions & Performance Data

d	50 mm	Bore diameter
D	80 mm	Outside diameter
B	16 mm	Width
C _r	31.500 N	Basic dynamic load rating, radial
C _{0r}	9.900 N	Basic static load rating, radial
C _{ur}	500 N	Fatigue load limit, radial
n _{G Grease}	32.000 1/min	Limiting speed for grease lubrication
n _{G Oil}	50.000 1/min	Limiting speed for oil lubrication
≈m	259,1 g	Weight



Mounting dimensions

d_a	56 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	74 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,3 mm	Maximum recess radius
$E_{tk \min}$	61,2 mm	Minimum diameter injection pitch
$E_{tk \max}$	63 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	58,8 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	63 mm	Maximum diameter injection pitch
a	17,9 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
α	17 °	Contact angle

Temperature range





T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.



Additional information

F_{VL}	49 N	Preload force light
F_{VM}	129 N	Preload force medium
F_{VH}	271 N	Preload force heavy
K_{aEL}	143 N	Lift-off force light
K_{aEM}	384 N	Lift-off force medium
K_{aEH}	825 N	Lift-off force heavy
c_{aL}	45 N/ μm	Axial rigidity light
c_{aM}	64 N/ μm	Axial rigidity medium
c_{aH}	86 N/ μm	Axial rigidity heavy

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed