



FAG

**HCM71916-C-T-P4S-UL-XL**

High speed spindle bearing

High speed spindle bearing HCM719...-C, adjusted, in pairs or sets, contact angle  $\alpha = 17^\circ$ , with ceramic balls, restricted tolerances

X-life

## Technical information





## Your current product variant

Preload class	L	Preload light
Contact angle	Contact angle $17^\circ$	Contact angle $17^\circ$
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing

## Main Dimensions &amp; Performance Data

d	80 mm	Bore diameter
D	110 mm	Outside diameter
B	16 mm	Width
$C_r$	28.000 N	Basic dynamic load rating, radial
$C_{0r}$	16.600 N	Basic static load rating, radial
$C_{ur}$	1.330 N	Fatigue load limit, radial
$n_G$ Grease	22.000 1/min	Limiting speed for grease lubrication
$n_G$ Oil	32.000 1/min	Limiting speed for oil lubrication
$\approx m$	284 g	Weight





### Mounting dimensions

$d_a$	86 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	104 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	0,6 mm	Maximum recess radius
$r_{a1 \max}$	0,3 mm	Maximum recess radius
$E_{tk \min}$	89,3 mm	Minimum diameter injection pitch
$E_{tk \max}$	92,1 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	85,7 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	92,1 mm	Maximum diameter injection pitch
$a$	22,5 mm	Distance between the apexes of the pressure cones

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
$\alpha$	17 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.



### Additional information

$F_{VL}$	128 N	Preload force light
$F_{VM}$	338 N	Preload force medium
$F_{VH}$	709 N	Preload force heavy
$K_{aEL}$	373 N	Lift-off force light
$K_{aEM}$	1.006 N	Lift-off force medium
$K_{aEH}$	2.173 N	Lift-off force heavy
$c_{aL}$	71 N/ $\mu$ m	Axial rigidity light
$c_{aM}$	102 N/ $\mu$ m	Axial rigidity medium
$c_{aH}$	137 N/ $\mu$ m	Axial rigidity heavy

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed