


**FAG****HCM7012-C-2RSD-T-P4S-UL-XL**

High speed spindle bearing

High speed spindle bearing HCM70.-
C-2RSD, adjusted, in pairs or sets, contact
angle $\alpha = 17^\circ$, with ceramic balls, lip seals on
both sides, non-contact, restricted tolerances

Technical information

**Your current product variant**

Preload	L	Preload light
Contact angle	Contact angle 17°	Contact angle 17°
Sealing	2RSD	Non-contact sealed on both sides and greased "for life"
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	60 mm	Bore diameter
D	95 mm	Outside diameter
B	18 mm	Width
C_r	19.800 N	Basic dynamic load rating, radial
C_{0r}	11.100 N	Basic static load rating, radial
C_{ur}	890 N	Fatigue load limit, radial
n_G Grease	26.000 1/min	Limiting speed for grease lubrication
$\approx m$	400 g	Weight



Mounting dimensions

d_a	67 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	88 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,6 mm	Maximum recess radius
a	20,8 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
α	17 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	80 °C	Operating temperature max.

Additional information

F_{VL}	86 N	Preload force light
F_{VM}	226 N	Preload force medium
F_{VH}	474 N	Preload force heavy
K_{aEL}	249 N	Lift-off force light
K_{aEM}	673 N	Lift-off force medium
K_{aEH}	1.453 N	Lift-off force heavy
c_{aL}	57 N/μm	Axial rigidity light
c_{aM}	81 N/μm	Axial rigidity medium
c_{aH}	110 N/μm	Axial rigidity heavy



Characteristics



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides