

**FAG****VCM7013-C-T-P4S-UL-XL**

High speed spindle bearing

High speed spindle bearing VCM70..-C, adjusted, in pairs or sets, contact angle $\alpha = 17^\circ$, with ceramic balls, rings made from Vacrodur, restricted tolerances

Technical information

**Your current product variant**

Contact angle	Contact angle 17°	Contact angle 17°
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to DIN 620
Arrangement bearing set	U	Single bearing
Preload	L	Preload light

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	100 mm	Outside diameter
B	18 mm	Width
C _r	48.000 N	Basic dynamic load rating, radial
C _{0r}	16.300 N	Basic static load rating, radial
C _{ur}	830 N	Fatigue load limit, radial
n _G Grease	26.000 1/min	Limiting speed for grease lubrication
n _G Oil	40.000 1/min	Limiting speed for oil lubrication
≈m	417,13 g	Weight



Mounting dimensions

d_a	72 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	93 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,6 mm	Maximum recess radius
$E_{tk \min}$	77,7 mm	Minimum diameter injection pitch
$E_{tk \max}$	80 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	74,7 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	80 mm	Maximum diameter injection pitch
a	21,6 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
α	17 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.



Additional information

F_{VL}	81 N	Preload force light
F_{VM}	213 N	Preload force medium
F_{VH}	446 N	Preload force heavy
K_{aEL}	234 N	Lift-off force light
K_{aEM}	631 N	Lift-off force medium
K_{aEH}	1.358 N	Lift-off force heavy
c_{aL}	59 N/ μ m	Axial rigidity light
c_{aM}	84 N/ μ m	Axial rigidity medium
c_{aH}	113 N/ μ m	Axial rigidity heavy

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed