

**FAG****1312-K-TVH-C3**

Self-aligning ball bearing

Self-aligning ball bearing 13..-K-TVH, tapered bore taper 1:12, plastic cage

## Technical information



## Your current product variant

|                           |              |  |
|---------------------------|--------------|--|
| Bore type                 | K            | Tapered, taper 1:12                                      |
| Type of Seal              | Without      | Not sealed   |
| Cage                      | TVH          | Solid cage made of glass-fiber reinforced polyamide PA66 |
| Tolerance class           | PN           | Normal (ISO 492:2023)                                    |
| Radial internal clearance | C3 (Group 3) | Internal clearance larger than CN                        |
| Lubricant                 | Without      | Bearing not greased                                      |

## Main Dimensions &amp; Performance Data

|             |             |                                   |
|-------------|-------------|-----------------------------------|
| d           | 60 mm       | Bore diameter                     |
| D           | 130 mm      | Outside diameter                  |
| B           | 31 mm       | Width                             |
| $C_r$       | 58.000 N    | Basic dynamic load rating, radial |
| $C_{0r}$    | 20.800 N    | Basic static load rating, radial  |
| $C_{ur}$    | 1.320 N     | Fatigue load limit, radial        |
| $n_G$       | 5.500 1/min | Limiting speed                    |
| $n_{gR}$    | 5.200 1/min | Reference speed                   |
| $\approx m$ | 1,938 kg    | Weight                            |



### Mounting dimensions

|              |        |                                       |
|--------------|--------|---------------------------------------|
| $d_{a \min}$ | 72 mm  | Minimum diameter shaft shoulder       |
| $d_{a \max}$ | 83 mm  | Maximum diameter shaft shoulder       |
| $D_{a \max}$ | 118 mm | Maximum diameter of housing shoulder  |
| $d_{b \min}$ | 65 mm  | Minimum cavity diameter of the sleeve |
| $B_{a \min}$ | 6 mm   | Minimum cavity width of the sleeve    |
| $r_{a \max}$ | 2,1 mm | Maximum fillet radius                 |

### Dimensions

|            |          |                              |
|------------|----------|------------------------------|
| $r_{\min}$ | 2,1 mm   | Minimum chamfer dimension    |
| $D_1$      | 112,2 mm | Shoulder diameter outer ring |
| $d_1$      | 87 mm    | Shoulder diameter inner ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |  |
|-------|------|--|
| $e$   | 0,23 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,78 | Dynamic axial load factor  |
| $Y_2$ | 4,3  | Dynamic axial load factor  |
| $Y_0$ | 2,91 | Static axial load factor   |

### Additional information

H312

Adapter sleeve



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment