



**FAG****QJ1040-MPA**

Four-point contact bearing

Four point contact bearing QJ10..-MPA, solid brass cage

Technical information

**Your current product variant**

Cage	MPA	Solid brass cage, outer ring guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	200 mm	Bore diameter
D	310 mm	Outside diameter
B	51 mm	Width
C_r	390.000 N	Basic dynamic load rating, radial
C_{0r}	620.000 N	Basic static load rating, radial
C_{ur}	22.000 N	Fatigue load limit, radial
n_G	3.600 1/min	Limiting speed
n_{gr}	1.890 1/min	Reference speed
m	15 kg	Weight

Mounting dimensions

$d_{a \min}$	210,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	299,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum fillet radius



Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
D_1	271,5 mm	Shoulder diameter outer ring
d_1	238,88 mm	Shoulder diameter inner ring
a	178,6 mm	Distance between the apexes of the pressure cones
α	35 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed