



**FAG****QJ1060-MPA**

Four-point contact bearing

Four point contact bearing QJ10..-MPA, solid brass cage

Technical information

**Your current product variant**

Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	300 mm	Bore diameter
D	460 mm	Outside diameter
B	74 mm	Width
C_r	630.000 N	Basic dynamic load rating, radial
C_{0r}	1.250.000 N	Basic static load rating, radial
C_{ur}	35.000 N	Fatigue load limit, radial
n_G	2.360 1/min	Limiting speed
n_{gr}	1.160 1/min	Reference speed
m	47,7 kg	Weight

Mounting dimensions

$d_{a \min}$	314,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	445,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum fillet radius










Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
D_1	406 mm	Shoulder diameter outer ring
d_1	356,4 mm	Shoulder diameter inner ring
a	266,1 mm	Distance between the apexes of the pressure cones
α	35 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing