

**FAG****QJ10/560-N2-MPA**

Four-point contact bearing

Four point contact bearing QJ10..-N2-MPA,
holding grooves, solid brass cage

Technical information



Your current product variant

Design, bearing outer ring	N2	Two retaining grooves in the outer ring on one side
Cage	MPA	Solid brass cage, outer ring guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	560 mm	Bore diameter
D	820 mm	Outside diameter
B	115 mm	Width
C _r	1.310.000 N	Basic dynamic load rating, radial
C _{0r}	3.800.000 N	Basic static load rating, radial
C _{ur}	79.000 N	Fatigue load limit, radial
n _G	1.260 1/min	Limiting speed
n _{gr}	495 1/min	Reference speed
≈m	220 kg	Weight

Mounting dimensions

d _{a min}	583 mm	Minimum diameter shaft shoulder
D _{a max}	797 mm	Maximum diameter of housing shoulder
r _{a max}	5 mm	Maximum fillet radius










Dimensions

r_{\min}	6 mm	Minimum chamfer dimension
D_1	730,9 mm	Shoulder diameter outer ring
d_1	652,7 mm	Shoulder diameter inner ring
a	483,1 mm	Distance between the apexes of the pressure cones
a_n	25 mm	Height retaining slot
b_n	20,5 mm	Width retaining slot
r_n	3 mm	Radius retaining slot
	45 °	Angle retaining slot
α	35 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing