



**FAG****QJ1272-MPA**

Four-point contact bearing

Four point contact bearing QJ12...-MPA, solid brass cage

## Technical information

**Your current product variant**

Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Axial internal clearance	CN	Group N (CN)

**Main Dimensions & Performance Data**

d	360 mm	Bore diameter
D	650 mm	Outside diameter
B	122 mm	Width
$C_r$	1.110.000 N	Basic dynamic load rating, radial
$C_{0r}$	2.600.000 N	Basic static load rating, radial
$C_{ur}$	67.000 N	Fatigue load limit, radial
$n_G$	1.700 1/min	Limiting speed
$n_{gr}$	810 1/min	Reference speed
$m$	192 kg	Weight

**Mounting dimensions**

$d_{a \min}$	386 mm	Minimum diameter shaft shoulder
$D_{a \max}$	624 mm	Maximum diameter of housing shoulder
$r_{a \max}$	5 mm	Maximum fillet radius










### Dimensions

$r_{min}$	6 mm	Minimum chamfer dimension
$D_1$	544,2 mm	Shoulder diameter outer ring
$d_1$	469,9 mm	Shoulder diameter inner ring
$a$	505 mm	Distance between the apexes of the pressure cones
$\alpha$	45 °	Contact angle

### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	200 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing