

**FAG****QJ1256-N2-MPA-C3**

Four-point contact bearing

Four point contact bearing QJ12...-N2-MPA,  
holding grooves, solid brass cage

## Technical information



## Your current product variant

Design, bearing outer ring	N2	Two retaining grooves in the outer ring on one side
Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Axial internal clearance	C3	Group 3 (C3), bigger than CN

## Main Dimensions &amp; Performance Data

d	280 mm	Bore diameter
D	500 mm	Outside diameter
B	90 mm	Width
C <sub>r</sub>	790.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.600.000 N	Basic static load rating, radial
C <sub>ur</sub>	45.500 N	Fatigue load limit, radial
n <sub>G</sub>	2.240 1/min	Limiting speed
n <sub>gr</sub>	1.110 1/min	Reference speed
≈m	81,8 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	300 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	480 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	4 mm	Maximum fillet radius



## Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
$D_1$	420,8 mm	Shoulder diameter outer ring
$d_1$	362,45 mm	Shoulder diameter inner ring
$a$	390 mm	Distance between the apexes of the pressure cones
$a_n$	15 mm	Height retaining slot
$b_n$	12,5 mm	Width retaining slot
$r_n$	2,5 mm	Radius retaining slot
	45 °	Angle retaining slot
$\alpha$	45 °	Contact angle

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

## Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing