



**FAG****QJ222-MPA**

Four-point contact bearing

Four point contact bearing QJ2..-MPA, solid brass cage

## Technical information

**Your current product variant**

Cage	MPA	Solid brass cage, outer ring guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	CN	Group N (CN)

**Main Dimensions & Performance Data**

d	110 mm	Bore diameter
D	200 mm	Outside diameter
B	38 mm	Width
$C_r$	249.000 N	Basic dynamic load rating, radial
$C_{0r}$	285.000 N	Basic static load rating, radial
$C_{ur}$	12.700 N	Fatigue load limit, radial
$n_G$	5.900 1/min	Limiting speed
$n_{gr}$	3.350 1/min	Reference speed
$m$	5,66 kg	Weight

**Mounting dimensions**

$d_{a \min}$	122 mm	Minimum diameter shaft shoulder
$D_{a \max}$	188 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum fillet radius



### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$D_1$	169,8 mm	Shoulder diameter outer ring
$d_1$	141,74 mm	Shoulder diameter inner ring
$a$	108,5 mm	Distance between the apexes of the pressure cones
$\alpha$	35 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed