

**FAG****QJ238-N2-MPA**

Four-point contact bearing

Four point contact bearing QJ2..-N2-MPA,
holding grooves, solid brass cage

Technical information

Your current product variant



Design, bearing outer ring	N2	Two retaining grooves in the outer ring on one side
Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	190 mm	Bore diameter
D	340 mm	Outside diameter
B	55 mm	Width
C_r	460.000 N	Basic dynamic load rating, radial
C_{0r}	740.000 N	Basic static load rating, radial
C_{ur}	25.000 N	Fatigue load limit, radial
n_G	3.400 1/min	Limiting speed
n_{gr}	1.760 1/min	Reference speed
$\approx m$	23,489 kg	Weight

Mounting dimensions

$d_{a \text{ min}}$	207 mm	Minimum diameter shaft shoulder
$D_{a \text{ max}}$	323 mm	Maximum diameter of housing shoulder
$r_{a \text{ max}}$	3 mm	Maximum fillet radius





Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
D_1	286,3 mm	Shoulder diameter outer ring
d_1	245,8 mm	Shoulder diameter inner ring
a	185,6 mm	Distance between the apexes of the pressure cones
a_n	12,7 mm	Hight retaining slot
b_n	10,5 mm	Width retaining slot
r_n	2 mm	Radius retaining slot
	45 °	Angle retaining slot
α	35 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing