



FAG

QJ205-XL-MPA-C2

Four-point contact bearing

Four point contact bearing QJ2...-XL-MPA, X-life, solid brass cage

X-life

Technical information



Your current product variant

Cage	MPA	Solid brass cage, outer ring guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	C2	Group 2 (C2), smaller than CN

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	52 mm	Outside diameter
B	15 mm	Width
C _r	26.000 N	Basic dynamic load rating, radial
C _{0r}	18.800 N	Basic static load rating, radial
C _{ur}	1.300 N	Fatigue load limit, radial
n _G	28.000 1/min	Limiting speed
n _{gr}	12.300 1/min	Reference speed
m	0,159 kg	Weight

Mounting dimensions

d _{a min}	31 mm	Minimum diameter shaft shoulder
D _{a max}	46 mm	Maximum diameter of housing shoulder
r _{a max}	1 mm	Maximum fillet radius









Dimensions

r_{min}	1 mm	Minimum chamfer dimension
D_1	43,06 mm	Shoulder diameter outer ring
d_1	33,94 mm	Shoulder diameter inner ring
a	27 mm	Distance between the apexes of the pressure cones
α	35 °	Contact angle

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed