



FAG

**QJ206-XL-MPA-P6-C3**

Four-point contact bearing

Four point contact bearing QJ2..-XL-MPA, X-life, solid brass cage

X-life

## Technical information



## Your current product variant

Tolerance class	P6	Class 6 (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	C3	Group 3 (C3), bigger than CN

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	62 mm	Outside diameter
B	16 mm	Width
C <sub>r</sub>	37.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	27.500 N	Basic static load rating, radial
C <sub>ur</sub>	1.930 N	Fatigue load limit, radial
n <sub>G</sub>	23.200 1/min	Limiting speed
n <sub>gr</sub>	10.200 1/min	Reference speed
m	0,24 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	36 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	56 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1 mm	Maximum fillet radius



### Dimensions

$r_{min}$	1 mm	Minimum chamfer dimension
$D_1$	50,65 mm	Shoulder diameter outer ring
$d_1$	40,35 mm	Shoulder diameter inner ring
$a$	31,9 mm	Distance between the apexes of the pressure cones
$\alpha$	35 °	Contact angle

### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	150 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed