



FAG

**QJ217-XL-MPA**

Four-point contact bearing

Four point contact bearing QJ2..-XL-MPA, X-life, solid brass cage

X-life

## Technical information



## Your current product variant

Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	CN	Group N (CN)

## Main Dimensions &amp; Performance Data

d	85 mm	Bore diameter
D	150 mm	Outside diameter
B	28 mm	Width
$C_r$	158.000 N	Basic dynamic load rating, radial
$C_{0r}$	160.000 N	Basic static load rating, radial
$C_{ur}$	11.100 N	Fatigue load limit, radial
$n_G$	8.800 1/min	Limiting speed
$n_{gr}$	4.050 1/min	Reference speed
$m$	2,174 kg	Weight

## Mounting dimensions

$d_{a \min}$	96 mm	Minimum diameter shaft shoulder
$D_{a \max}$	139 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2 mm	Maximum fillet radius



## Dimensions

$r_{\min}$	2 mm	Minimum chamfer dimension
$D_1$	128,6 mm	Shoulder diameter outer ring
$d_1$	107,6 mm	Shoulder diameter inner ring
$a$	82,3 mm	Distance between the apexes of the pressure cones
$\alpha$	35 °	Contact angle

## Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

## Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed