

**FAG****QJ332-N2-MPA-C4**

Four-point contact bearing

Four point contact bearing QJ3..-N2-MPA,
holding grooves, solid brass cage

Technical information



Your current product variant

Design, bearing outer ring	N2	Two retaining grooves in the outer ring on one side
Tolerance class	PN	Normal (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Axial internal clearance	C4	Group 4 (C4), bigger than C3

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	340 mm	Outside diameter
B	68 mm	Width
C _r	580.000 N	Basic dynamic load rating, radial
C _{0r}	870.000 N	Basic static load rating, radial
C _{ur}	30.000 N	Fatigue load limit, radial
n _G	3.350 1/min	Limiting speed
n _{gr}	1.680 1/min	Reference speed
≈m	32,8 kg	Weight

Mounting dimensions

d _{a min}	177 mm	Minimum diameter shaft shoulder
D _{a max}	323 mm	Maximum diameter of housing shoulder
r _{a max}	3 mm	Maximum fillet radius










Dimensions

r_{min}	4 mm	Minimum chamfer dimension
D_1	279,9 mm	Shoulder diameter outer ring
d_1	222,74 mm	Shoulder diameter inner ring
a	175,1 mm	Distance between the apexes of the pressure cones
a_n	12,7 mm	Hight retaining slot
b_n	10,5 mm	Width retaining slot
r_n	2 mm	Radius retaining slot
	45 °	Angle retaining slot
α	35 °	Contact angle

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	200 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing