



FAG

**QJ304-XL-MPA**

Four-point contact bearing

Four point contact bearing QJ3..-XL-MPA, X-life, solid brass cage

X-life

## Technical information



## Your current product variant

Cage	MPA	Solid brass cage, outer ring guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	CN	Group N (CN)

## Main Dimensions &amp; Performance Data

d	20 mm	Bore diameter
D	52 mm	Outside diameter
B	15 mm	Width
C <sub>r</sub>	31.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	19.600 N	Basic static load rating, radial
C <sub>ur</sub>	1.360 N	Fatigue load limit, radial
n <sub>G</sub>	28.500 1/min	Limiting speed
n <sub>gr</sub>	10.700 1/min	Reference speed
m	0,175 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	27 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	45 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1 mm	Maximum fillet radius









### Dimensions

$r_{min}$	1,1 mm	Minimum chamfer dimension
$D_1$	41,38 mm	Shoulder diameter outer ring
$d_1$	30,62 mm	Shoulder diameter inner ring
$a$	25,2 mm	Distance between the apexes of the pressure cones
$\alpha$	35 °	Contact angle

### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	150 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed