

**FAG****QJ304-XL-MPA-P6-C3**

Four-point contact bearing

Four point contact bearing QJ3.-XL-MPA, X-life, solid brass cage

X-life

Technical information



Your current product variant

Tolerance class	P6	Class 6 (ISO 492:2023)
Cage	MPA	Solid brass cage, outer ring guided
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	C3	Group 3 (C3), bigger than CN

Main Dimensions & Performance Data

d	20 mm	Bore diameter
D	52 mm	Outside diameter
B	15 mm	Width
C_r	31.000 N	Basic dynamic load rating, radial
C_{0r}	19.600 N	Basic static load rating, radial
C_{ur}	1.360 N	Fatigue load limit, radial
n_G	28.500 1/min	Limiting speed
n_{gr}	10.700 1/min	Reference speed
m	0,175 kg	Weight

Mounting dimensions

$d_{a \min}$	27 mm	Minimum diameter shaft shoulder
$D_{a \max}$	45 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius









Dimensions

r_{min}	1,1 mm	Minimum chamfer dimension
D_1	41,38 mm	Shoulder diameter outer ring
d_1	30,62 mm	Shoulder diameter inner ring
a	25,2 mm	Distance between the apexes of the pressure cones
α	35 °	Contact angle

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed