

**FAG****QJ1021-XL-N2-MPA-C4**

Four-point contact bearing

Four point contact ball bearing QJ10..-XL-N2-MPA, X-life, holding grooves, solid brass cage

Technical information



Your current product variant

Design, bearing outer ring	N2	Two retaining grooves in the outer ring on one side
Cage	MPA	Solid brass cage, outer ring guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Axial internal clearance	C4	Group 4 (C4), bigger than C3

Main Dimensions & Performance Data

d	105 mm	Bore diameter
D	160 mm	Outside diameter
B	26 mm	Width
C _r	126.000 N	Basic dynamic load rating, radial
C _{0r}	145.000 N	Basic static load rating, radial
C _{ur}	8.700 N	Fatigue load limit, radial
n _G	8.100 1/min	Limiting speed
n _{gr}	3.550 1/min	Reference speed
≈m	2,035 kg	Weight

Mounting dimensions

d _{a min}	114 mm	Minimum diameter shaft shoulder
D _{a max}	151 mm	Maximum diameter of housing shoulder
r _{a max}	2 mm	Maximum fillet radius



Dimensions

r_{\min}	2 mm	Minimum chamfer dimension
D_1	141,45 mm	Shoulder diameter outer ring
d_1	124,6 mm	Shoulder diameter inner ring
a	92,8 mm	Distance between the apexes of the pressure cones
a_n	6,5 mm	Hight retaining slot
b_n	6,5 mm	Width retaining slot
r_n	0,5 mm	Radius retaining slot
	45 °	Angle retaining slot
α	35 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed