



FAG

QJ213-XL-MPA-S1

Four-point contact bearing

Four point contact bearing QJ2..-XL-MPA, X-life, solid brass cage

X-life

Technical information



Your current product variant

Cage	MPA	Solid brass cage, outer ring guided
Tolerance class	PN	Tolerance class PN, acc. to DIN 620
Dimensional / heat stabilization	S1	Rings dimensional stabilized up to 200°
Axial internal clearance	CN	Group N (CN)

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	120 mm	Outside diameter
B	23 mm	Width
C_r	106.000 N	Basic dynamic load rating, radial
C_{0r}	104.000 N	Basic static load rating, radial
C_{ur}	7.200 N	Fatigue load limit, radial
n_G	11.300 1/min	Limiting speed
n_{gr}	4.900 1/min	Reference speed
m	1,223 kg	Weight

Mounting dimensions

$d_{a \min}$	74 mm	Minimum diameter shaft shoulder
$D_{a \max}$	111 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum fillet radius



Dimensions

r_{\min}	1,5 mm	Minimum chamfer dimension
D_1	101,45 mm	Shoulder diameter outer ring
d_1	84,15 mm	Shoulder diameter inner ring
a	64,8 mm	Distance between the apexes of the pressure cones
α	35 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed