

**FAG****N207-E-XL-TVP2** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing N2..-E-TVP, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N2

Technical information

**Your current product variant**

| | | |
|---------------------------|--------------|----------------------------------|
| Cage | TVP2 | Solid Window Cage made from PA66 |
| Tolerance class | PN | Normal (ISO 492:2023) |
| Change mark | E | Increased Capacity Design |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Number of rows | 1 | Single-row design |

Main Dimensions & Performance Data

| | | |
|--------------------------|--------------|---------------------------------------|
| d | 35 mm | Bore diameter |
| D | 72 mm | Outside diameter |
| B | 17 mm | Width |
| C _r | 59.000 N | Basic dynamic load rating, radial |
| C _{0r} | 50.000 N | Basic static load rating, radial |
| C _{ur} | 7.800 N | Fatigue load limit, radial |
| n _G Grease | 12.000 1/min | Limiting speed for grease lubrication |
| n _G Oil | 14.100 1/min | Limiting speed for oil lubrication |
| ≈m | 0,304 kg | Weight |

Mounting dimensions

| | | |
|---------------------|-------|------------------------------|
| d _a | 39 mm | Diameter shaft shoulder |
| D _a | 65 mm | Diameter of housing shoulder |
| r _{a1} max | 1 mm | Maximum recess radius |



Dimensions

| | | |
|---------------------|--------|-----------------------------|
| $r_{1 \text{ min}}$ | 0,6 mm | Minimum chamfer dimension |
| s_1 | 0,7 mm | Axial displacement |
| E | 64 mm | Raceway diameter outer ring |

Temperature range

| | | |
|------------------|--------|----------------------------|
| T_{min} | -30 °C | Operating temperature min. |
| T_{max} | 120 °C | Operating temperature max. |

Characteristics

-  F_r Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed