

**FAG****N208-E-XL-M1** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing N2..-M1, with cage,
single row, non-locating bearing, 0 ribs on
outer ring, 2 rib on inner ring, type N2

Technical information

**Your current product variant**

Cage	M1	Two Piece Brass Cage Roller Guided
Tolerance class	PN	Normal (ISO 492:2023)
Change mark	E	Increased Capacity Design
Radial internal clearance	CN (Group N)	Normal internal clearance
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	80 mm	Outside diameter
B	18 mm	Width
C _r	63.000 N	Basic dynamic load rating, radial
C _{0r}	53.000 N	Basic static load rating, radial
C _{ur}	8.400 N	Fatigue load limit, radial
n _G Grease	14.200 1/min	Limiting speed for grease lubrication
≈m	0,421 kg	Weight

Mounting dimensions

d _a	47 mm	Diameter shaft shoulder
D _a	73 mm	Diameter of housing shoulder

Dimensions

E	71,5 mm	Raceway diameter outer ring
---	---------	-----------------------------



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed