

**FAG****N313-E-XL-M1** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing N3..-E-M1, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N3

## Technical information

**Your current product variant**

Cage	M1	Two Piece Brass Cage Roller Guided
Tolerance class	PN	Normal (ISO 492:2023)
Change mark	E	Increased Capacity Design
Radial internal clearance	CN (Group N)	Normal internal clearance
Number of rows	1	Single-row design

**Main Dimensions & Performance Data**

d	65 mm	Bore diameter
D	140 mm	Outside diameter
B	33 mm	Width
C <sub>r</sub>	21.400 N	Basic dynamic load rating, radial
C <sub>0r</sub>	191.000 N	Basic static load rating, radial
C <sub>ur</sub>	34.500 N	Fatigue load limit, radial
≈m	2,462 kg	Weight

**Mounting dimensions**

D <sub>a</sub>	128 mm	Diameter of housing shoulder
r <sub>a1 max</sub>	2 mm	Maximum recess radius

**Dimensions**

r <sub>1 min</sub>	2,1 mm	Minimum chamfer dimension
E	124,5 mm	Raceway diameter outer ring



### Temperature range

---

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	150 °C	Operating temperature max.

### Characteristics

---

-   $F_r$  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed