

**FAG****N321-E-XL-M1** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing N3..-E-M1, with cage, single row, non-locating bearing, 0 ribs on outer ring, 2 rib on inner ring, type N3

Technical information

**Your current product variant**

Cage	M1	Two Piece Brass Cage Roller Guided
Tolerance class	PN	Normal (PN)
Change mark	E	Increased Capacity Design
Radial internal clearance	CN (Group N)	Normal internal clearance
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	105 mm	Bore diameter
D	225 mm	Outside diameter
B	49 mm	Width
C_r	495.000 N	Basic dynamic load rating, radial
C_{0r}	470.000 N	Basic static load rating, radial
C_{ur}	79.000 N	Fatigue load limit, radial
$\approx m$	9,907 kg	Weight

Mounting dimensions

D_a	211 mm	Diameter of housing shoulder
$r_{a1 \max}$	2,5 mm	Maximum recess radius

Dimensions

$r_{1 \min}$	3 mm	Minimum chamfer dimension
E	201 mm	Raceway diameter outer ring



Temperature range

T_{\min} -30 °C Operating temperature min.

T_{\max} 150 °C Operating temperature max.

Characteristics



Radial load



Grease Lubrication



Oil Lubrication



Not sealed