**FAG****NU2080-E-M1A** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Technical information

Your current product variant

Design	E	Increased Capacity Design
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	400 mm	Bore diameter
D	600 mm	Outside diameter
B	118 mm	Width
C _r	2.280.000 N	Basic dynamic load rating, radial
C _{0r}	4.450.000 N	Basic static load rating, radial
C _{ur}	415.000 N	Fatigue load limit, radial
n _G	1.730 1/min	Limiting speed
n _{gr}	660 1/min	Reference speed
≈m	121,03 kg	Weight



Mounting dimensions

$d_{a \min}$	417 mm	Minimum diameter shaft shoulder
$d_{a \max}$	446 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	454 mm	Minimum shaft shoulder
$D_{a \max}$	583 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
$r_{a1 \max}$	4 mm	Maximum recess radius




Dimensions

r_{\min}	5 mm	Minimum chamfer dimension
$r_{1 \min}$	5 mm	Minimum chamfer dimension
s	9,8 mm	Axial displacement
E	550 mm	Raceway diameter outer ring
F	450 mm	Raceway diameter inner ring
$D_{1 \min}$	533,6 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed