

**FAG****NU2252-E-M1A-C3** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

## Technical information

**Your current product variant**

Design	E	Increased Capacity Design
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

**Main Dimensions & Performance Data**

d	260 mm	Bore diameter
D	480 mm	Outside diameter
B	130 mm	Width
$C_r$	2.180.000 N	Basic dynamic load rating, radial
$C_{0r}$	3.350.000 N	Basic static load rating, radial
$C_{ur}$	350.000 N	Fatigue load limit, radial
$n_G$	2.060 1/min	Limiting speed
$n_{gr}$	780 1/min	Reference speed
$m$	107,51 kg	Weight



### Mounting dimensions

$d_{a \min}$	280 mm	Minimum diameter shaft shoulder
$d_{a \max}$	310 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	316 mm	Minimum shaft shoulder
$D_{a \max}$	460 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
$r_{a1 \max}$	4 mm	Maximum recess radius

### Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
$r_{1 \min}$	5 mm	Minimum chamfer dimension
s	10,5 mm	Axial displacement
E	433 mm	Raceway diameter outer ring
F	313 mm	Raceway diameter inner ring
$D_{1 \min}$	409 mm	Minimum rib diameter outer ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed