

**FAG****NU272-E-M1A-C3** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-M1A, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Technical information

Your current product variant

Design	E	Increased Capacity Design
Cage	M1A	Two Piece Brass Cage Lip guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	360 mm	Bore diameter
D	650 mm	Outside diameter
B	95 mm	Width
C_r	1.990.000 N	Basic dynamic load rating, radial
C_{0r}	3.150.000 N	Basic static load rating, radial
C_{ur}	224.000 N	Fatigue load limit, radial
n_G	1.570 1/min	Limiting speed
n_{gr}	700 1/min	Reference speed
m	149 kg	Weight



Mounting dimensions

$d_{a \min}$	386 mm	Minimum diameter shaft shoulder
$d_{a \max}$	447 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	455 mm	Minimum shaft shoulder
$D_{a \max}$	624 mm	Maximum diameter of housing shoulder
$r_{a \max}$	5 mm	Maximum recess radius
$r_{a1 \max}$	5 mm	Maximum recess radius

Dimensions

r_{\min}	6 mm	Minimum chamfer dimension
$r_{1 \min}$	6 mm	Minimum chamfer dimension
s	9,5 mm	Axial displacement
E	579 mm	Raceway diameter outer ring
F	451 mm	Raceway diameter inner ring
$D_{1 \min}$	558,5 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

-  F_r Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed