



FAG

**NU216-E-XL-M1-C4**

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

## Technical information



## Your current product variant

|                           |              |                                    |
|---------------------------|--------------|------------------------------------|
| Design                    | E            | Increased Capacity Design          |
| Cage                      | M1           | Two Piece Brass Cage Roller Guided |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3  |
| Tolerance class           | PN           | Normal (ISO 492:2023)              |
| Number of rows            | 1            | Single-row design                  |

## Main Dimensions &amp; Performance Data

|          |             |                                   |
|----------|-------------|-----------------------------------|
| d        | 80 mm       | Bore diameter                     |
| D        | 140 mm      | Outside diameter                  |
| B        | 26 mm       | Width                             |
| $C_r$    | 166.000 N   | Basic dynamic load rating, radial |
| $C_{0r}$ | 168.000 N   | Basic static load rating, radial  |
| $C_{ur}$ | 23.100 N    | Fatigue load limit, radial        |
| $n_G$    | 9.000 1/min | Limiting speed                    |
| $n_{gr}$ | 4.200 1/min | Reference speed                   |
| $m$      | 1,7 kg      | Weight                            |



### Mounting dimensions

|               |        |                                      |
|---------------|--------|--------------------------------------|
| $d_{a \min}$  | 91 mm  | Minimum diameter shaft shoulder      |
| $d_{a \max}$  | 94 mm  | Maximum diameter of shaft shoulder   |
| $d_{b \min}$  | 97 mm  | Minimum shaft shoulder               |
| $D_{a \max}$  | 129 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$  | 2 mm   | Maximum recess radius                |
| $r_{a1 \max}$ | 2 mm   | Maximum recess radius                |

### Dimensions

|              |           |                                 |
|--------------|-----------|---------------------------------|
| $r_{\min}$   | 2 mm      | Minimum chamfer dimension       |
| $r_{1 \min}$ | 2 mm      | Minimum chamfer dimension       |
| s            | 1,3 mm    | Axial displacement              |
| E            | 125,3 mm  | Raceway diameter outer ring     |
| F            | 95,3 mm   | Raceway diameter inner ring     |
| $D_{1 \min}$ | 120,45 mm | Minimum rib diameter outer ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 150 °C | Operating temperature max. |

### Characteristics

|   |                    |
|---|--------------------|
|  | Radial load        |
|  | Grease Lubrication |
|  | Oil Lubrication    |
|  | Not sealed         |