



FAG

**NU2211-E-XL-TVP2**

Cylindrical roller bearing

Cylindrical roller bearing NU..-E-XL-TVP2, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

## Technical information



## Your current product variant

|                           |              |                                  |
|---------------------------|--------------|----------------------------------|
| Design                    | E            | Increased Capacity Design        |
| Cage                      | TVP2         | Solid Window Cage made from PA66 |
| Radial internal clearance | CN (Group N) | Normal internal clearance        |
| Tolerance class           | PN           | Normal (ISO 492:2023)            |
| Number of rows            | 1            | Single-row design                |

## Main Dimensions &amp; Performance Data

|             |              |                                   |
|-------------|--------------|-----------------------------------|
| d           | 55 mm        | Bore diameter                     |
| D           | 100 mm       | Outside diameter                  |
| B           | 25 mm        | Width                             |
| $C_r$       | 117.000 N    | Basic dynamic load rating, radial |
| $C_{0r}$    | 118.000 N    | Basic static load rating, radial  |
| $C_{ur}$    | 21.000 N     | Fatigue load limit, radial        |
| $n_G$       | 10.000 1/min | Limiting speed                    |
| $n_{gr}$    | 4.700 1/min  | Reference speed                   |
| $\approx m$ | 0,744 kg     | Weight                            |



### Mounting dimensions

|               |        |                                      |
|---------------|--------|--------------------------------------|
| $d_{a \min}$  | 62 mm  | Minimum diameter shaft shoulder      |
| $d_{a \max}$  | 65 mm  | Maximum diameter of shaft shoulder   |
| $d_{b \min}$  | 68 mm  | Minimum shaft shoulder               |
| $D_{a \max}$  | 91 mm  | Maximum diameter of housing shoulder |
| $r_{a \max}$  | 1,5 mm | Maximum recess radius                |
| $r_{a1 \max}$ | 1 mm   | Maximum recess radius                |

### Dimensions

|              |         |                                 |
|--------------|---------|---------------------------------|
| $r_{\min}$   | 1,5 mm  | Minimum chamfer dimension       |
| $r_{1 \min}$ | 1,1 mm  | Minimum chamfer dimension       |
| s            | 1,3 mm  | Axial displacement              |
| E            | 90 mm   | Raceway diameter outer ring     |
| F            | 66 mm   | Raceway diameter inner ring     |
| $D_{1 \min}$ | 86,6 mm | Minimum rib diameter outer ring |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Characteristics

|   |                    |
|---|--------------------|
|  | Radial load        |
|  | Grease Lubrication |
|  | Oil Lubrication    |
|  | Not sealed         |