

**FAG****NU3044-M1** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing NU..-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

Technical information



Your current product variant

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	220 mm	Bore diameter
D	340 mm	Outside diameter
B	90 mm	Width
C_r	960.000 N	Basic dynamic load rating, radial
C_{0r}	1.730.000 N	Basic static load rating, radial
C_{ur}	209.000 N	Fatigue load limit, radial
n_G	3.150 1/min	Limiting speed
n_{gr}	1.250 1/min	Reference speed
$\approx m$	30,46 kg	Weight



Mounting dimensions

$d_{a \min}$	232 mm	Minimum diameter shaft shoulder
$d_{a \max}$	246 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	254 mm	Minimum shaft shoulder
$D_{a \max}$	328 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$r_{a1 \max}$	2,5 mm	Maximum recess radius

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
$r_{1 \min}$	3 mm	Minimum chamfer dimension
s	8,8 mm	Axial displacement
E	310 mm	Raceway diameter outer ring
F	250 mm	Raceway diameter inner ring
$D_{1 \min}$	298,9 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed