



FAG

NU422-XL-M1-C3

Cylindrical roller bearing

Cylindrical roller bearing NU..-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Technical information



Your current product variant

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	280 mm	Outside diameter
B	65 mm	Width
C_r	680.000 N	Basic dynamic load rating, radial
C_{0r}	660.000 N	Basic static load rating, radial
C_{ur}	80.000 N	Fatigue load limit, radial
n_G	4.450 1/min	Limiting speed
n_{gr}	2.550 1/min	Reference speed
m	21,75 kg	Weight



Mounting dimensions

$d_{a \min}$	130 mm	Minimum diameter shaft shoulder
$d_{a \max}$	153 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	157 mm	Minimum shaft shoulder
$D_{a \max}$	260 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
$r_{a1 \max}$	3 mm	Maximum recess radius

Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
$r_{1 \min}$	4 mm	Minimum chamfer dimension
s	6,2 mm	Axial displacement
E	235 mm	Raceway diameter outer ring
F	155 mm	Raceway diameter inner ring
$D_{1 \min}$	220,9 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed