

**FAG****NU264-EX-TB-M1** [↗](#)

## Cylindrical roller bearing

Cylindrical roller bearing NU2..-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

## Technical information



## Your current product variant

Design	EX	Increased Capacity Design Design Modified
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rolling element rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	320 mm	Bore diameter
D	580 mm	Outside diameter
B	92 mm	Width
C <sub>r</sub>	1.810.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	2.700.000 N	Basic static load rating, radial
C <sub>ur</sub>	190.000 N	Fatigue load limit, radial
n <sub>G</sub>	1.730 1/min	Limiting speed
n <sub>gr</sub>	830 1/min	Reference speed
m	112,9 kg	Weight



### Mounting dimensions

$d_{a \min}$	340 mm	Minimum diameter shaft shoulder
$d_{a \max}$	388,5 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	395,5 mm	Minimum shaft shoulder
$D_{a \max}$	560 mm	Maximum diameter of housing shoulder
$r_{a \max}$	4 mm	Maximum recess radius
$r_{a1 \max}$	4 mm	Maximum recess radius

### Dimensions

$r_{\min}$	5 mm	Minimum chamfer dimension
$r_{1 \min}$	5 mm	Minimum chamfer dimension
s	7,5 mm	Axial displacement
E	520 mm	Raceway diameter outer ring
F	392 mm	Raceway diameter inner ring
$D_{1 \min}$	494,4 mm	Minimum rib diameter outer ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing