



**FAG****NJ332-E-M1-C3**

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Technical information



Your current product variant

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	340 mm	Outside diameter
B	68 mm	Width
C_r	860.000 N	Basic dynamic load rating, radial
C_{0r}	1.060.000 N	Basic static load rating, radial
C_{ur}	130.000 N	Fatigue load limit, radial
n_G	3.000 1/min	Limiting speed
n_{gr}	1.770 1/min	Reference speed
$\approx m$	31,44 kg	Weight



Mounting dimensions

$d_{a \text{ min}}$	177 mm	Minimum diameter shaft shoulder
$d_{a \text{ max}}$	200 mm	Maximum diameter of shaft shoulder
$D_{a \text{ max}}$	323 mm	Maximum diameter of housing shoulder
$d_{c \text{ min}}$	228 mm	Minimum shaft shoulder
$r_{a \text{ max}}$	3 mm	Maximum recess radius

Dimensions

r_{min}	4 mm	Minimum chamfer dimension
$r_{1 \text{ min}}$	4 mm	Minimum chamfer dimension
s	5,6 mm	Axial displacement
E	300 mm	Raceway diameter outer ring
F	204 mm	Raceway diameter inner ring
$D_{1 \text{ min}}$	286 mm	Minimum rib diameter outer ring
d_1	221,6 mm	Maximum rib diameter inner ring

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Additional information

HJ332-E

L-washer



Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing