



FAG

**NJ211-E-XL-TVP2-C4**

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-TVP2, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

## Technical information



## Your current product variant

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	55 mm	Bore diameter
D	100 mm	Outside diameter
B	21 mm	Width
C <sub>r</sub>	99.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	95.000 N	Basic static load rating, radial
C <sub>ur</sub>	16.400 N	Fatigue load limit, radial
n <sub>G</sub>	10.000 1/min	Limiting speed
n <sub>gr</sub>	5.800 1/min	Reference speed
m	0,67 kg	Weight



### Mounting dimensions

$d_{a \min}$	62 mm	Minimum diameter shaft shoulder
$d_{a \max}$	65 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	91 mm	Maximum diameter of housing shoulder
$d_{c \min}$	73 mm	Minimum shaft shoulder
$r_{a \max}$	1,5 mm	Maximum recess radius

### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
s	0,8 mm	Axial displacement
E	90 mm	Raceway diameter outer ring
F	66 mm	Raceway diameter inner ring
$D_{1 \min}$	86,6 mm	Minimum rib diameter outer ring
$d_1$	70,8 mm	Maximum rib diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Additional information

HJ211-E

L-washer

### Characteristics

-   $F_r$  Radial load
-   $F_a$  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed