



FAG

NJ213-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-TVP2,
with cage, single row, semi-locating bearing,
2 ribs on outer ring, 1 rib on inner ring, type
NJ

X-life

Technical information



Your current product variant

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	120 mm	Outside diameter
B	23 mm	Width
C _r	128.000 N	Basic dynamic load rating, radial
C _{0r}	120.000 N	Basic static load rating, radial
C _{ur}	21.000 N	Fatigue load limit, radial
n _G	8.100 1/min	Limiting speed
n _{gr}	4.900 1/min	Reference speed
≈m	1,05 kg	Weight



Mounting dimensions

$d_{a \min}$	74 mm	Minimum diameter shaft shoulder
$d_{a \max}$	77 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	111 mm	Maximum diameter of housing shoulder
$d_{c \min}$	87 mm	Minimum shaft shoulder
$r_{a \max}$	1,5 mm	Maximum recess radius

Dimensions

r_{\min}	1,5 mm	Minimum chamfer dimension
$r_{1 \min}$	1,5 mm	Minimum chamfer dimension
s	1,4 mm	Axial displacement
E	108,5 mm	Raceway diameter outer ring
F	78,5 mm	Raceway diameter inner ring
$D_{1 \min}$	104,3 mm	Minimum rib diameter outer ring
d_1	84,4 mm	Maximum rib diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

HJ213-E

L-washer

Characteristics



Radial load



Axial load in one direction



Grease Lubrication



Oil Lubrication



Not sealed