



FAG

**NJ2312-E-XL-TVP2-C3**

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-TVP2,  
with cage, single row, semi-locating bearing,  
2 ribs on outer ring, 1 rib on inner ring, type  
NJ

X-life

## Technical information



## Your current product variant

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	60 mm	Bore diameter
D	130 mm	Outside diameter
B	46 mm	Width
C <sub>r</sub>	265.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	260.000 N	Basic static load rating, radial
C <sub>ur</sub>	50.000 N	Fatigue load limit, radial
n <sub>G</sub>	7.400 1/min	Limiting speed
n <sub>gr</sub>	4.250 1/min	Reference speed
m	2,79 kg	Weight



### Mounting dimensions

$d_{a \min}$	72 mm	Minimum diameter shaft shoulder
$d_{a \max}$	75 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	118 mm	Maximum diameter of housing shoulder
$d_{c \min}$	86 mm	Minimum shaft shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius

### Dimensions

$r_{\min}$	2,1 mm	Minimum chamfer dimension
$r_{1 \min}$	2,1 mm	Minimum chamfer dimension
s	3,5 mm	Axial displacement
E	115 mm	Raceway diameter outer ring
F	77 mm	Raceway diameter inner ring
$D_{1 \min}$	109,6 mm	Minimum rib diameter outer ring
$d_1$	84,4 mm	Maximum rib diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Additional information


HJ2312-E

L-washer

### Characteristics



Radial load



Axial load in one direction



Grease Lubrication



Oil Lubrication



Not sealed