



FAG

NJ311-E-XL-TVP2 [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-TVP2,
with cage, single row, semi-locating bearing,
2 ribs on outer ring, 1 rib on inner ring, type
NJ

X-life

Technical information



Your current product variant

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	55 mm	Bore diameter
D	120 mm	Outside diameter
B	29 mm	Width
C _r	159.000 N	Basic dynamic load rating, radial
C _{0r}	139.000 N	Basic static load rating, radial
C _{ur}	25.500 N	Fatigue load limit, radial
n _G	8.000 1/min	Limiting speed
n _{gr}	5.500 1/min	Reference speed
m	1,48 kg	Weight



Mounting dimensions

$d_{a \min}$	66 mm	Minimum diameter shaft shoulder
$d_{a \max}$	69 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	109 mm	Maximum diameter of housing shoulder
$d_{c \min}$	80 mm	Minimum shaft shoulder
$r_{a \max}$	2 mm	Maximum recess radius

Dimensions

r_{\min}	2 mm	Minimum chamfer dimension
$r_{1 \min}$	2 mm	Minimum chamfer dimension
s	1,8 mm	Axial displacement
E	106,5 mm	Raceway diameter outer ring
F	70,5 mm	Raceway diameter inner ring
$D_{1 \min}$	101,4 mm	Minimum rib diameter outer ring
d_1	77,5 mm	Maximum rib diameter inner ring

Temperature range


T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

HJ311-E

L-washer

Characteristics




Radial load



Axial load in one direction



Grease Lubrication



Oil Lubrication



Not sealed