

**FAG****NJ1021-XL-M1** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing NJ..-XL-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

X-life

Technical information

Your current product variant

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	105 mm	Bore diameter
D	160 mm	Outside diameter
B	26 mm	Width
C _r	132.000 N	Basic dynamic load rating, radial
C _{0r}	154.000 N	Basic static load rating, radial
C _{ur}	24.400 N	Fatigue load limit, radial
n _G	8.400 1/min	Limiting speed
n _{gr}	4.050 1/min	Reference speed
m	1,87 kg	Weight



Mounting dimensions

$d_{a \min}$	111 mm	Minimum diameter shaft shoulder
$d_{a \max}$	118 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	151 mm	Maximum diameter of housing shoulder
$d_{c \min}$	126 mm	Minimum shaft shoulder
$r_{a \max}$	2 mm	Maximum recess radius

Dimensions

r_{\min}	2 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
s	3,2 mm	Axial displacement
E	145,5 mm	Raceway diameter outer ring
F	119,5 mm	Raceway diameter inner ring
$D_{1 \min}$	141 mm	Minimum rib diameter outer ring
d_1	124,5 mm	Maximum rib diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed