

**FAG****NJ208-E-XL-TVP2-C4**

Cylindrical roller bearing

Cylindrical roller bearing NJ..-E-XL-TVP2, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

Technical information



Your current product variant

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Tolerance class	PN	Normal (PN)
Number of rolling element rows	1	Single-row design

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	80 mm	Outside diameter
B	18 mm	Width
C_r	63.000 N	Basic dynamic load rating, radial
C_{0r}	53.000 N	Basic static load rating, radial
C_{ur}	8.500 N	Fatigue load limit, radial
n_G	12.500 1/min	Limiting speed
n_{gr}	7.500 1/min	Reference speed
$\approx m$	0,378 kg	Weight



Mounting dimensions

$d_{a \min}$	47 mm	Minimum diameter shaft shoulder
$d_{a \max}$	49 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	73 mm	Maximum diameter of housing shoulder
$d_{c \min}$	56 mm	Minimum shaft shoulder
$r_{a \max}$	1 mm	Maximum recess radius

Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
$r_1 \min$	1,1 mm	Minimum chamfer dimension
s	1 mm	Axial displacement
E	71,5 mm	Raceway diameter outer ring
F	49,5 mm	Raceway diameter inner ring
$D_1 \min$	68,3 mm	Minimum rib diameter outer ring
d_1	54 mm	Maximum rib diameter inner ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

HJ208-E

L-washer

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed