



FAG

**NUP2328-E-XL-M1** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing NUP.-E-XL-M1, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

## Technical information



## Your current product variant

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rolling element rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	140 mm	Bore diameter
D	300 mm	Outside diameter
B	102 mm	Width
C <sub>r</sub>	1.210.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.390.000 N	Basic static load rating, radial
C <sub>ur</sub>	221.000 N	Fatigue load limit, radial
n <sub>G</sub>	3.950 1/min	Limiting speed
n <sub>gr</sub>	1.620 1/min	Reference speed
≈m	37,2 kg	Weight



### Mounting dimensions

$d_1$	195,4 mm	Maximum rib diameter inner ring
$D_{1 \text{ min}}$	251,7 mm	Minimum rib diameter outer ring
$d_{a \text{ min}}$	157 mm	Minimum diameter shaft shoulder
$d_{c \text{ min}}$	198 mm	Minimum shaft shoulder
$D_{a \text{ max}}$	283 mm	Maximum diameter of housing shoulder
$r_{a \text{ max}}$	3 mm	Maximum recess radius

### Dimensions

$r_{\text{min}}$	4 mm	Minimum chamfer dimension
$r_{1 \text{ min}}$	4 mm	Minimum chamfer dimension
E	264 mm	Raceway diameter outer ring
F	180 mm	Raceway diameter inner ring
$B_3$	16 mm	Width of loose rib

### Temperature range

$T_{\text{min}}$	-30 °C	Operating temperature min.
$T_{\text{max}}$	150 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed