


**FAG****NUP2330-E-XL-M1** [↗](#)

Cylindrical roller bearing

Cylindrical roller bearing NUP.-E-XL-M1, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

**X-life**

## Technical information



## Your current product variant

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	150 mm	Bore diameter
D	320 mm	Outside diameter
B	108 mm	Width
C <sub>r</sub>	1.380.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	1.600.000 N	Basic static load rating, radial
C <sub>ur</sub>	249.000 N	Fatigue load limit, radial
n <sub>G</sub>	3.650 1/min	Limiting speed
n <sub>gr</sub>	1.460 1/min	Reference speed
≈m	44,7 kg	Weight



### Mounting dimensions

$d_1$	209,5 mm	Maximum rib diameter inner ring
$D_1 \text{ min}$	269,8 mm	Minimum rib diameter outer ring
$d_a \text{ min}$	167 mm	Minimum diameter shaft shoulder
$d_c \text{ min}$	213 mm	Minimum shaft shoulder
$D_a \text{ max}$	303 mm	Maximum diameter of housing shoulder
$r_a \text{ max}$	3 mm	Maximum recess radius








### Dimensions

$r_{\text{min}}$	4 mm	Minimum chamfer dimension
$r_1 \text{ min}$	4 mm	Minimum chamfer dimension
E	283 mm	Raceway diameter outer ring
F	193 mm	Raceway diameter inner ring
$B_3$	16,5 mm	Width of loose rib

### Temperature range

$T_{\text{min}}$	-30 °C	Operating temperature min.
$T_{\text{max}}$	150 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing