



FAG


NUP330-E-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NUP.-E-XL-M1, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

Technical information



Your current product variant

Design	E	Increased Capacity Design
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rolling element rows	1	Single-row design

Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	320 mm	Outside diameter
B	65 mm	Width
C _r	900.000 N	Basic dynamic load rating, radial
C _{0r}	930.000 N	Basic static load rating, radial
C _{ur}	141.000 N	Fatigue load limit, radial
n _G	3.650 1/min	Limiting speed
n _{gR}	1.940 1/min	Reference speed
≈m	26,8 kg	Weight



Mounting dimensions

d_1	209,5 mm	Maximum rib diameter inner ring
$D_{1 \text{ min}}$	269,8 mm	Minimum rib diameter outer ring
$d_{a \text{ min}}$	167 mm	Minimum diameter shaft shoulder
$d_{c \text{ min}}$	213 mm	Minimum shaft shoulder
$D_{a \text{ max}}$	303 mm	Maximum diameter of housing shoulder
$r_{a \text{ max}}$	3 mm	Maximum recess radius

Dimensions

r_{min}	4 mm	Minimum chamfer dimension
$r_{1 \text{ min}}$	4 mm	Minimum chamfer dimension
E	283 mm	Raceway diameter outer ring
F	193 mm	Raceway diameter inner ring
B_3	10 mm	Width of loose rib

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	150 °C	Operating temperature max.

Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing