

**FAG****NU4956-S-K-M-SP**

Cylindrical roller bearing

Super precision cylindrical roller bearings
 NNU49..-S-K-M-SP, non-locating bearing,
 double row, with tapered bore, taper 1:12,
 separable, with cage

Technical information



Your current product variant

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Locating Feature , bearing outer ring	S	Lubrication holes and lubrication groove in outer ring
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	280 mm	Bore diameter
D	380 mm	Outside diameter
B	100 mm	Width
C _r	770.000 N	Basic dynamic load rating, radial
C _{0r}	1.790.000 N	Basic static load rating, radial
C _{ur}	198.000 N	Fatigue load limit, radial
n _{G Grease}	1.970 1/min	Limiting speed for grease lubrication
n _{G Oil}	2.320 1/min	Limiting speed for oil lubrication
≈m	44 kg	Weight



Mounting dimensions

d_a	309,4 mm	Diameter shaft shoulder
	h12	Diameter shaft shoulder tolerance
D_a	354 mm	Diameter of housing shoulder
	H12	Diameter of housing shoulder tolerance
$r_{a1 \max}$	2,1 mm	Maximum recess radius






Dimensions

$r_{1 \min}$	2,1 mm	Minimum chamfer dimension
F	312 mm	Raceway diameter inner ring
n_s	15 mm	Width of lubricating groove
d_s	8 mm	Diameter lubrication hole
s	5,4 mm	Axial displacement

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing