


**FAG****NU4980-S-K-M-SP**

Cylindrical roller bearing

Super precision cylindrical roller bearings
 NNU49..-S-K-M-SP, non-locating bearing,
 double row, with tapered bore, taper 1:12,
 separable, with cage

Technical information



Your current product variant

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Locating Feature , bearing outer ring	S	Lubrication holes and lubrication groove in outer ring
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	400 mm	Bore diameter
D	540 mm	Outside diameter
B	140 mm	Width
C _r	1.490.000 N	Basic dynamic load rating, radial
C _{0r}	3.800.000 N	Basic static load rating, radial
C _{ur}	390.000 N	Fatigue load limit, radial
n _{G Grease}	1.330 1/min	Limiting speed for grease lubrication
n _{G Oil}	1.570 1/min	Limiting speed for oil lubrication
≈m	89,11 kg	Weight



Mounting dimensions

d_a	442,6 mm	Diameter shaft shoulder
	h12	Diameter shaft shoulder tolerance
D_a	502 mm	Diameter of housing shoulder
	H12	Diameter of housing shoulder tolerance
$r_{a1 \max}$	3 mm	Maximum recess radius






Dimensions

$r_{1 \min}$	4 mm	Minimum chamfer dimension
F	446 mm	Raceway diameter inner ring
n_s	17,7 mm	Width of lubricating groove
d_s	9,5 mm	Diameter lubrication hole
s	7,2 mm	Axial displacement

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing