

FAG


NN3008-D-K-TVP-SP-XL

Cylindrical roller bearing

Super precision cylindrical roller bearings
 NN30...-D-K-TVP-SP, Non-locating bearing,
 double row, with tapered bore, taper 1:12,
 separable, with cage

X-life

Technical information



Your current product variant

Cage	TVP	Plastic cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Change mark	D	Internal Variant D
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	68 mm	Outside diameter
B	21 mm	Width
C_r	46.500 N	Basic dynamic load rating, radial
C_{0r}	52.000 N	Basic static load rating, radial
C_{ur}	8.400 N	Fatigue load limit, radial
$n_{G Grease}$	16.200 1/min	Limiting speed for grease lubrication
$n_{G Oil}$	19.100 1/min	Limiting speed for oil lubrication
m	0,281 kg	Weight



Mounting dimensions

d_a	49 mm	Diameter shaft shoulder
	h_{12}	Diameter shaft shoulder tolerance
D_a	62,6 mm	Diameter of housing shoulder
	H_{12}	Shoulder diameter outer ring clearance
$E_{tk1\ nom}$	59,8 mm	Injection pitch diameter min
$r_{a1\ max}$	1 mm	Maximum recess radius




Dimensions

$r_{1\ min}$	1 mm	Minimum chamfer dimension
E	61 mm	Raceway diameter outer ring
s	1,7 mm	Axial displacement

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed